

# Personal Wireless Gas Monitor with PID

## RAE Systems ToxiRAE Pro PID

The ToxiRAE Pro PID is the world's smallest wireless volatile organic compounds (VOC) monitor<sup>1,2</sup>. The ToxiRAE Pro PID takes worker protection to the next level by providing safety professionals wireless access to real-time instrument readings and alarm status from any location for better visibility and faster response. Featuring RAE Systems' next-generation PID sensor, the ToxiRAE Pro PID can promptly detect and accurately monitor over 300 VOCs. With an onboard library of 190 correction factors, the ToxiRAE Pro PID can be programmed to automatically read in concentrations of the specified compound.

### FEATURES

- World's smallest photoionization detector
- Wireless, wireless-capable, or non-wireless versions are available<sup>1,2,5</sup>
- Wireless elevates worker protection to the next level
- Cutting-edge PID with 0.1 to 2,000 ppm range, 0.1 ppm resolution<sup>3</sup> and 190 built-in correction factors
- Available in Industrial Hygiene (advanced) or Safety (basic)<sup>2</sup> configurations
- Wireless access to real-time instrument readings and alarm status from any location
- Unmistakable five-way local and remote wireless notification of alarm conditions
- Reliable, rugged, and intrinsically safe
- Largest display in its class
- Continuous datalogging<sup>3</sup>
- Fully automated bump testing and calibration with AutoRAE 2<sup>2</sup>
- User-replaceable sensor, filter, fan, and Lithium-ion battery

### APPLICATIONS

- Industrial hygiene and safety
  - Oil and gas
  - Chemical plants
  - Pharmaceutical plants
  - Government health, safety, security, and environmental agencies
  - Hazardous materials teams, first responders
- Environmental applications
  - Environmental consulting
  - Soil remediation



ToxiRAE Pro PID with and without the protective rubber boot



**CALL GEOTECH TODAY (800) 833-7958**

**Geotech Environmental Equipment, Inc.**

2650 East 40th Avenue • Denver, Colorado 80205

(303) 320-4764 • (800) 833-7958 • FAX (303) 322-7242

email: sales@geotechenv.com website: www.geotechenv.com

# Personal Wireless Gas Monitor with PID



## RAE Systems ToxiRAE Pro PID

### SPECIFICATIONS<sup>4</sup>

<b>Size</b>	4.6" H x 2.4" W x 1.2" D (118 x 60 x 30 mm)
<b>Weight</b>	8.29 oz. (235 g)
<b>Sensor</b>	Photoionization sensor with 10.6 eV (standard) or 9.8 eV <sup>2,3</sup> (optional) lamp. Response time (T <sub>90</sub> ) < 15 sec. (Isobutene). Field-replaceable sensor. Easy access to lamp for cleaning.
<b>Detectable Gases</b>	A wide variety of ionizable chemicals using 190 built-in and over 300 published correction factors
<b>Battery</b>	Rechargeable Lithium-ion battery - Operating time: > 12 hours (normal operation) - Recharge time: < 4 hours through charging cradle
<b>Display</b>	Graphical LCD display with white LED backlighting (activated when monitor is in alarm or with a button press)
<b>Display Readout</b>	- Real-time reading of VOC concentrations in parts per million or mg/m <sup>3</sup> ; battery status; data logging on/off; wireless on/off and reception quality - STEL, TWA, and peak values - Calibration and measurement gases; correction factors
<b>Keypad</b>	2 buttons for operation and programming
<b>Sampling</b>	Internal fan
<b>Calibration</b>	Automatic with AutoRAE 2 Test and Calibration Station <sup>2</sup> or manual
<b>Alarm Modes</b>	Wireless remote alarm notification <sup>1,2</sup> ; audible (95 dB @ 30 cm), vibration, visible alarm (flashing bright red LEDs), and on-screen indication of alarm conditions - High alarm: 3 beeps and flashes per second - Low alarm: 2 beeps and flashes per second - STEL and TWA: 1 beep and flash per second - Additional diagnostic alarm and display message for low battery and fan stall
<b>Datalogging</b>	Continuous datalogging <sup>3</sup> with a three-month capacity (at one-minute intervals) - User-configurable datalogging interval (from 1 to 3,600 seconds)
<b>Communication and Data Download</b>	- Data download and instrument set-up on PC via charging and PC comm. cradle - Data download via AutoRAE 2 Automated Test and Calibration Station <sup>2</sup> - Wireless data and status transmission <sup>1,2</sup> via built-in RF modem (optional)
<b>Wireless Network</b>	RAE Systems Dedicated Wireless Network
<b>Wireless Frequency<sup>1,2</sup></b>	ISM license-free bands
<b>Wireless Range<sup>1,2</sup> (Typical)</b>	300 feet (100 meters)
<b>Operating Temperature</b>	-4° to 131°F (-20° to 50°C)
<b>Humidity</b>	0% to 95% relative humidity (non-condensing)
<b>Dust and Water Resistance</b>	IP54 rating for dust and water ingress protection (validated by an independent test laboratory)
<b>Hazardous Location Approvals</b>	US and Canada: CSAUS Class I, Division 1, Groups A, B, C and D. T-code T4 Class I, Zone 0 A/Exia IIC T4 Europe: ATEX: CE, Ex II 1G, Ex ia IIC Ga T4 IECEX: Ex ia IIC Ga T4 China: Ex ia IIC T4
<b>CE Compliance (European Conformity)</b>	EMC directive: 2004/108/EC. R&TTE directive: 1999/5/EC. ATEX directive: 94/9/EC
<b>Warranty</b>	- Two years on non-consumable components - One year on sensor, fan, battery, and other consumable parts

### TOXIRAE PRO PID COMES WITH:

- ToxiRAE Pro PID monitor with sensor as specified, alligator clip, protective rubber boot, and rechargeable battery installed
- Charging and PC communication cradle
- PC communication cable
- AC adapter (100 to 240 V, 50/60 Hz AC to 12 V DC)
- Calibration adapter
- Combined instrument/sensor cap removal tool
- Quick Start Guide
- CD with documentation
- ProRAE Studio II software for PC-based instrument configuration and data management
- Technical Note TN-106 with ionization energies and correction factors for 300+ VOCs (Industrial Hygiene versions only)
- Calibration card, quality certificate, packing list, and warranty/registration card

### OPTIONAL ACCESSORIES

- AutoRAE 2 Automated Test and Calibration Station<sup>2</sup>
- Multi-unit charging station<sup>2</sup> for up to five monitors
- Contact Geotech for other accessories, maintenance kits, calibration gas, sensors, and replacement parts

### CONFIGURATIONS

- Industrial Hygiene (advanced) and Safety (basic)<sup>2</sup> configurations are available

#### Industrial Hygiene configurations:

- Advanced PID sensor (10.6 eV; 0.1 to 2,000 ppm; 0.1 ppm resolution)
- Datalogging
- 9.8 eV<sup>2,3</sup> or 10.6 eV lamp options

#### Safety configurations<sup>2</sup>:

- 10.6 eV; 1 to 1,000 ppm; 1 ppm resolution PID
- No datalogging
- 10.6 eV lamp option only

1 Wireless functionality is scheduled for availability in 2011 in North America and Europe. Contact Geotech for availability in other regions.

2 Contact Geotech for availability.

3 Available with Industrial Hygiene configurations only.

4 Specifications are subject to change.

5 Wireless units have a functioning RF modem and are ready for wireless deployments; Wireless-capable units can be upgraded to wireless in the field for a fee; Non-wireless units cannot be upgraded to wireless. Additional equipment and/or software licenses may be required to enable remote wireless monitoring and alarm transmission.

**CALL GEOTECH TODAY (800) 833-7958**

**Geotech Environmental Equipment, Inc.**

2650 East 40th Avenue • Denver, Colorado 80205

(303) 320-4764 • **(800) 833-7958** • FAX (303) 322-7242

email: sales@geotechenv.com website: www.geotechenv.com