

Portable Generators

Honda Super Quiet Generators

The Honda EU Series Super Quiet Generators represent the leading edge of portable power technology. Ranging from 1000 to 3000 watts, the Super Quiet Generators are ideal for a variety of applications.

FEATURES

- Protected by Oil Alert®
- Super quiet – fully enclosed for quieter operation
- Lightweight
- Advanced inverter for reliable power to computers and other sensitive equipment
- USDA-qualified spark arrester/muffler
- Eco Throttle (load dependent operation)



SPECIFICATIONS

Model No.	EU1000i	EU2000i	EU3000is
Engine	Honda GXH50	Honda GX100	Honda GX200
Displacement	50cc	98.5cc	196cc
AC Output	120V 1000W max. (8.3A) 900W rated (7.5A)	120V 2000W max. (16.7A) 1600W rated (13.3A)	120V 3000W max. (25A) 2800W rated (23.3A)
Receptacles*	B	C	C, F
DC Output	12V, 96W (8A)	12V, 96W (8A)	12V, 144W (12A)
Starting System	Recoil	Recoil	Recoil, electric
Fuel Tank Capacity	0.6 gal.	1.1 gal.	3.4 gal.
Run Time (full tank)	3.8 hrs. @ rated load, 8.3 hrs. @ ¼ load	4 hrs. @ rated load, 15 hrs. @ ¼ load	7.2 hrs. @ rated load, 20 hrs. @ ¼ load
Dimensions (L x W x H)	17.7" x 9.4" x 15.0"	20.1" x 11.4" x 16.7"	25.8" x 18.9" x 22.4"
Noise Level	59 dB @ rated load 53 dB @ ¼ load	59 dB @ rated load 53 dB @ ¼ load	58 dB @ rated load 49 dB @ ¼ load
Dry Weight	29 lbs.	46.3 lbs.	134 lbs.

B – 15A 125V Duplex C – 20A 125V Duplex F – 30A 125V Locking Plug

*Receptacle Descriptions

CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc.

2650 East 40th Avenue • Denver, Colorado 80205

(303) 320-4764 • **(800) 833-7958** • FAX (303) 322-7242

email: sales@geotechenv.com website: www.geotechenv.com