

# Selective Product Recovery

## GeoSorb Selective Product Recovery

The GeoSorb is designed to recover hydrocarbons from 2" or 4" (5cm or 10cm) and larger wells. The GeoSorb System consists of a stainless steel screened cage assembly and a product selective absorbent. The system is lowered down the well where it passively absorbs free product.



2" (5cm)  
Well Size

4" (10cm)  
Well Size

### FEATURES

- Designed for 2" (5cm) or 4" (10cm) and larger wells
- Designed to recover the product, not the water
- Absorbent sock refills available in cases of 12, or individually
- Heavy-duty #304 stainless steel screen assembly
- Teflon™ coated stainless steel hanger
- Ballast weight for optimal submergence

### OPERATION

*Prior to use, always check depth and thickness of product layer in well!*

#### Simple to use, just 4 easy steps:

1. Insert sock into stainless steel screen assembly. Do not lower sock down well without screen assembly.
2. Attach safety cable or cord to the hanger on the screen assembly.
3. Slowly lower into the well to maximize exposure to product layer. In long-term applications, set unit to accommodate water level fluctuations over the full length of screened assembly.
4. Retrieve screen assembly, remove used sock, dispose according to local ordinances.

### SPECIFICATIONS

	2" GeoSorb	4" GeoSorb
<b>Screen Material</b>	#304 SS, perforated	#304 SS, perforated
<b>Screen Mesh Holes Size</b>	5/32" dia. x 3/16" stg. ctrs. (3.97mm x 4.76mm)	5/32" dia. x 3/16" stg. ctrs. (3.97mm x 4.76mm)
<b>Available Screen Length</b>	36.0" (91.4cm)	36.0" (91.4cm)
<b>Screen Outside Diameter</b>	1.750" (44.5mm)	3.670" (93.2mm)
<b>Actual Overall Assy. Length</b>	37 1/8" (94.3cm)	36 5/8" (93.0cm)
<b>Weight w/Ballast</b>	1.73 lbs. (.78 kg)	5.19 lbs. (2.35 kg)
<b>Min. Well Inside Diameter</b>	2" (51mm)	4" (102mm)
<b>Absorbent Sock Diameter</b>	1.5" (38.1mm)	3.0" (76.2mm)
<b>Absorbent Sock Length</b>	36" (91.4cm)	36" (91.4cm)
<b>Absorbent Sock Material</b>	Polypropylene filler contained in a white polypropylene fabric sock	Polypropylene filler contained in a white polypropylene fabric sock
<b>Rated Absorption*</b>	2.16 gal. (8.2 L) per case of 12 .72 qt. (.68L) per sock	8.52 gal. (32.3L) per case of 12 2.8 qt. (2.65L) per sock

\*The product absorption rate is determined by the viscosity of the product and can vary depending on site conditions.

**CALL GEOTECH TODAY (800) 833-7958**

**Geotech Environmental Equipment, Inc.**

2650 East 40th Avenue • Denver, Colorado 80205

(303) 320-4764 • (800) 833-7958 • FAX (303) 322-7242

email: sales@geotechenv.com website: www.geotechenv.com